

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please cancel without prejudice or disclaimer claims 1-11 the underlying PCT application and ADD new claims 12-22 in accordance with the following:

Claims 1-11 (cancelled)

12. (New) A method for establishment of a communication link from a first telecommunication device to a second telecommunication device via a telecommunication network, comprising:

 sending a connection establishment message with a data object to the telecommunication network allocated to a first subscriber to establish the communication link;

 storing the data object via the telecommunication network on a data provision component;

 transmitting a call signaling message from the telecommunication network to the second telecommunication device providing reference information which refers to the data provision component on which the data object of the first subscriber has been stored;

 signaling the data provision component from the second telecommunication device by using the reference information requesting that the data provision component transmit the data object to the second telecommunication device allocated to the first subscriber;

 transmitting the data object from the data provision component to the second telecommunication device; and

 playing the data object at the second telecommunication device.

13. (New) The method according to claim 1, wherein the telecommunication network has a first subnetwork to which the first telecommunication device has been allocated and a second subnetwork to which the second telecommunication device has been allocated, the first and second subnetworks being connected with each other via a switching component.

14. (New) The method according to claim 2, wherein the switching component performs said storing and transmitting.

15. (New) The method according to claim 14, wherein the data provision component is arranged on a network based on an Internet protocol and connected to the switching component.

16. (New) The method according to claim 15, wherein the reference information has a uniform resource identifier.

17. (New) The method according to claim 16, wherein the second telecommunication device is in a communication session in accordance with a session initiation protocol.

18. (New) The method according to claim 17, wherein the switching component, as a call signaling message, sends an INVITE message to the second telecommunication device into which the reference information has been inserted.

19. (New) The method according to claim 18, wherein the data object includes picture information, tone information and text information.

20. (New) The method according to claim 19, wherein at least one of the first and second telecommunication devices is one of a mobile radio device, a mobile telephone and a computer with a radio module.

21. (New) The method according to claim 20, wherein the telecommunication network includes a mobile radio network functioning according to one of a global system for mobile communication standard and a universal mobile telecommunications system standard.

22. (New) A telecommunication system, comprising:
a telecommunication network;
a data provision component, connected to said telecommunication network; and
first and second telecommunication devices, said first telecommunication device establishing a communication link to said second telecommunication device via said telecommunication network by sending a connection establishment message with a data object

Serial No.:

to said telecommunication network allocated to a first subscriber to establish the communication link, said data provision component storing the data object, said telecommunication network transmitting a call signaling message to said second telecommunication device providing reference information which refers to the data provision component on which the data object of the first subscriber has been stored, said second telecommunication device signaling said data provision component using the reference information to request that said data provision component transmit the data object to said second telecommunication device allocated to the first subscriber, said data provision component transmitting the data object to said second telecommunication device and said second telecommunication device playing the data object.